



# 1915L 19-inch LCD

Touchscreen Monitor



**Integrated Touch**



**Commercial Grade**



**3-Year Warranty**

## Product Overview

The Elo 1915L standard format touchscreen monitor is built to withstand the rigors of continuous public use with a rugged built-for-touch design. Its stylish, thin and modern look, coupled with a retail-focused feature set and is an attractive solution for commercial touchscreen monitor needs. The 1915L can be used in a wide variety of environments with its ability to register inputs from a finger, gloved hand or soft stylus with a fast and accurate response. The touchmonitor is available with Elo's industry-leading touch technologies and multiple mounting options to support most application uses.

The Elo 1915L offers multiple mounting options to ensure installation flexibility including: wall- and pole-mount via standard VESA mount patterns as well as tabletop accommodations with the use of the desktop stand. Capped through-mount holes on the base of the touchmonitor ensure table-top security.

**Available with IntelliTouch® surface acoustic wave (SAW) or AccuTouch® five-wire resistive touch technologies, both with a dual serial/ USB touch interface.**

**Sealed touchscreen against dirt, dust and liquid**

**Controls on the side rather than the front, plus lockout function for public use**

## 1915L 19-inch Touchscreen Monitor

Specifications	
Model	1915L
Color	Dark gray
Active Display Area	14.8" x 11.9" / 376.3 mm x 301.1 mm
LCD Technology	Active matrix TFT LCD
Diagonal Size	19"
Aspect Ratio	5:4
Native Resolution	1280 x 1024
Other supported resolutions	1280 x 1024 at 60 or 75 Hz; 1152 x 864 at 75 Hz; 1024 x 768 at 60, 65, 70, or 75 Hz; 832 x 624 at 75 Hz (Mac); 800 x 600 at 56, 60, 72, or 75 Hz; 720 x 400 at 70 Hz; 720 x 350 at 70 Hz; 640 x 480 at 60, 66, 72, or 75 Hz
Number Of Colors	16.7 million
Brightness (Typical)	LCD panel: 250 nits; with AccuTouch: 187 nits; with IntelliTouch: 225 nits
Response Time (Tr + Tf) (Typical)	5 msec
Viewing Angle (Typical)	Horizontal: ±85° / 170° ; Vertical: ±80° / 160°
Contrast Ratio (Typical)	1000:1
On-Screen Display (OSD) controls	OSD buttons: menu, up, down, select, power; OSD: contrast, brightness, H/V position, RGB (color temp), clock, phase, sharpness, recall, language (English, German, Spanish, Japanese, French); OSD disable/enable: power, OSD menu
Video	Analog (no proprietary video card needed) Mini D-Sub 15-Pin VGA type Input Video Horizontal Sync frequency range: 31.5 - 80KHz Input Video Vertical Sync (frame rate) frequency range: 56.3-75Hz
Power	Internal AC, power cable-C5 type; Input voltage range: 100-240VAC, 50/60Hz Monitor input power connector: Coaxial power jack (2.0mm (+0.0 -0.1mm) pin outer diameter, 6.4mm (+/- 0.3mm) barrel inner diameter, 8.8mm (+/- 0.3mm) Barrel depth); Monitor input power signal specifications: 12VDC +/- 5% Optional external DC (external power adapter included with unit , P/N:E005277) Adapter input connector: IEC 60320 C14; Adapter input voltage range: 100-240VAC, 50/60Hz Power Consumption Monitor + 115Vac (Typical): ON: 12.76W; SLEEP: 0.63W; OFF: 0.38W
Mounting Options	100 mm VESA mount; Threaded-through mounting holes, under stand
Temperature	Operating: 0°C to 40°C / 32°F to 104°F; Storage: -20°C to 60°C / -4°F to 140°F
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95%
Dimensions (W x D x H)	16.9" x 14.9" x 8.2" / 429 mm x 379 mm x 207 mm)
Shipping Dimensions	21.28" x 19.50" x 11.23" / 540 mm x 495 mm x 285 mm
Weight	Unpackaged: 17.4 lbs / 7.9 kg; Packaged: 25.8 lbs / 11.7 kg
MTBF	50,000 hours demonstrated
Other features	Security lock receptacle
Warranty	3 years
Extended Warranty	4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125
Agency approvals	UL, cUL, FCC, CE, UKCA, VCCI, IC, RCM, Argentina S Mark, TUV, CCC, China RoHS
What's in the Box	User Guide CD Quick Installation Guide AC Power Cord mickey 1.8M BK EU/KOREA AC Power Cord UL/SP-030+IS-034 1.8M BK Cable A55336-000 USB A-B 1830mmBK Cable DSUB-9PX2 1800mm BK W/PEBAG Cable VGA PC99 1.8M BK

## Ordering Information

Model	Part Number	Technology	Surface Treatment	Interface	Color
1915L	E607608	AccuTouch	Antiglare	Serial/USB	Dark Gray
	E266835	IntelliTouch	Antiglare	Serial/USB	Dark Gray

To find out more about our extensive range of Elo touch solutions, go to [elotouch.com](http://elotouch.com), or call the office nearest you.

### Elo Touch Solutions - Italy

Camax DS Srl  
Via Fratelli Di Dio, 18  
20063 Cernusco Sul Naviglio (MI)

Tel. +39 02 9544951  
Fax +39 02 9522671  
info@camax.it - [www.camax.it](http://www.camax.it)



Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2018 Elo Touch Solutions, Inc. All rights reserved. 18021AES00105